

Trio 200|250|300 Stretch Film

Why choose this product?

- + All-round stretch film
- + High stretch percentage

These product are the general purpose cast stretch films within the Trio assortment.

Technical specification

Item no	Thickness	Pre stretch	Width	Length	Colour	Cling	Reels/ pallet	Reels gross weight
Trio 300								
16890	12 µm	180 %	500 mm	3000 m	Transp.	Inside	30	17,3 kg
16895	15 µm	200 %	500 mm	2400 m	Transp.	Inside	30	17,3 kg
16900	17 µm	250 %	500 mm	2100 m	Transp.	Inside	30	17,2 kg
16905	20 µm	275 %	500 mm	1800 m	Transp.	Inside	30	17,3 kg
16910	23 µm	300 %	500 mm	1550 m	Transp.	Inside	30	17,2 kg
Trio 250								
16751	17 µm	200 %	500 mm	2100 m	Transp.	Inside	30	17,2 kg
16752	20 µm	225 %	500 mm	1800 m	Transp.	Inside	30	17,3 kg
16753	23 µm	250 %	500 mm	1550 m	Transp.	Inside	30	17,2 kg
Trio 200								
16617	17 µm	175 %	500 mm	2100 m	Transp.	Inside	30	17,2 kg
16620	20 µm	190 %	500 mm	1800 m	Transp.	Inside	30	17,3 kg
16623	23 µm	200 %	500 mm	1550 m	Transp.	Inside	30	17,2 kg
Special								
2829	23 µm	-	500 mm	1550 m	Black	Inside	30	17,3 kg
2813	23 µm	-	500 mm	1550 m	White	Inside	30	17,9 kg

Data is only intended for information and could be changed without previous notice. Every endeavour has been made to ensure that the information given herein is true and reliable but is given only for guidance. The tests are performed at 23 °C temperature (+/- 2 degrees). The roll gross weight has a tolerance of +/- 4 %

